



Metro Bleecker

White Oak

Character Grade

Brushed Surface

Matte Low VOC Waterbase Poly, UV Cured



SURFACES & FINISHES

Our Metro materials are finished with a low VOC water-based polyurethane that is ultra-violet cured. Depending on the color/style, Metro materials' surface textures are either lightly brushed or smooth.



DIMENSIONS & FORMATS

Metro material are available in an engineered format only.

ENGINEERED WOOD

3/4" Thickness

Standard plank widths are 5", 7", or 8"

* Wider plank options available upon request

Standard plank lengths are 1' – 7' random lengths

* A length upgrade of 3'-8' is available upon request

All metro materials have a 4 mm hardwood top layer

Plank & pattern OPTIONS

Single-width planks

Mixed-width planks

Herringbone

* Available in select colors only



INSTALLATION METHODS

Installation methods vary depending on wood format and site conditions, but here are some general guidelines:

Solid wood

is typically nailed, or nailed and glued, to a plywood subfloor.

Engineered wood

is typically glued down to concrete or plywood subfloors, with or without an underlayment such as a sound abating mat or a moisture barrier, depending on site conditions/requirements.

Engineered floors

are also usually the best choice for gluing down over radiant heat installations.

In either format,

when planks are particularly wide, gluing and nailing is always good practice if possible.

NYC SHOWROOM

24 WEST 20TH ST, NEW YORK, NY 10011

T 212.627.9663

E NYC@LVWOOD.COM

BOZEMAN SHOWROOM

38 N TRACY ST, BOZEMAN, MT, 59715

T 406.631.9663

E WEST@LVWOOD.COM

LVWOOD.COM